

ZAF1032

HD1080P WDR Analog Explosion Proof / Marine corrosion proof Camera with infrared lights



ZUOAN

Certificate	
Certificate Mark	Exd IIC T6 Gb / Ext D A21 IP68 T80℃
Certificate No	CNEx16.0708
Standards	Q/320412ZAF032-2016
Mechanical	
Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	2pcs G3/4 or NPT3/4
Sun-shield	Yes
Electrical	
Voltage	AC85V~AC265V or DC24V or AC24V
Power	15W/25W (with thermostat)
Surge Protect	Optional, TVS6000V surge protect
Ambient	
Ambient temperature	-25 to +60℃ / -45 to +80℃
Air pressure	80Kpa to 106Kpa
Relative Humidity	≦95% (no condensation)
Lights	
Lights	0-20m or 20-60 infrared lights
Lights Control	Support
Communication	
Communication	support analog video output
485 Communication	Support Pelco-D, Pelco-P
Communicate Rate	2400 to 19200bps
Camera	
Image Sensor	2.0 Megapixel high-performance CMOS
lens	2.8-12mm@ F1.4
Effective pixel	PAL 1956*1266
Min. Illumination	Color 0.01Lux 0Lux with IR
Shutter Time	1/50(1/60) sec~ 1/50,000 sec
Day&Night	Auto ICR
S/N ratio	>62dB (AGC off)

WDR	120dB true WDR
HD Video Output	1 Analog HD output
Synchronization	Internal Synchronization
CVBS Output	1Vp-p Composite Output(75Ω/BNC)
Control	
Gain	off/ lower/ higher
White Balance	ATW/AWC-SET/MANUAL
Private	ON/OFF, 8 programmable privacy masks
D/N Mode	Auto / Color / B/W
Motion Detection	4 programmable motion areas
Function	Defog, Mirror, Defective Pixel Correction, Sharpness, Cam
Scene	Indoor/outdoor/indoor1/low light
General	
Cable	integrated cable
Size	390*249*170mm
Weight	11.7kg
Mount	wall, pole
Wall Bracket	ZAZ100B

Dimension

